

Robotics Service Bus - Bug #2601

Options of logger styles do not work as expected

07/13/2016 04:48 PM - N. Köster

Status:	Resolved	Start date:	07/13/2016
Priority:	Normal	Due date:	
Assignee:	J. Moringen	% Done:	100%
Category:	Common Lisp Tools	Estimated time:	0.00 hour
Target version:			
Description			
Some options of logger styles do not work as expected.			

Associated revisions

Revision b92c2ce2 - 07/13/2016 04:55 PM - J. Moringen

Fixed comparison of symbol values in `src/formatting/protocol.lisp`

refs #2601

- `src/formatting/protocol.lisp` (`value< symbol symbol`): new method; compare symbols by name

Revision 553713e8 - 07/13/2016 04:55 PM - J. Moringen

Fixed `:columns` initarg processing in `src/formatting/event-style-monitor.lisp`

fixes #2601

The problem was that `'monitor-style-mixin'` uses a function that creates a set of columns whenever a monitor line is created. To allow supplying column specifications via the `:columns` initarg, such specifications have to be transformed into a suitable function.

- `src/formatting/event-style-monitor.lisp` (`monitor-style-mixin::columns`): removed initarg; added `style-%columns` accessor
(`monitor-style-mixin`): removed `:columns` default initarg
(`initialize-instance :before monitor-style-mixin`): new method; make sure that at least one of the `columns` and `default-columns` initargs is supplied
(`shared-initialize :after monitor-style-mixin t`): new method; if necessary, transform list of column specification into column creation function
- `src/formatting/event-style-monitor.lisp` (`define-monitor-style`): use `:default-columns` initarg instead of `:columns`
(`style-monitor/scope/tree`): likewise
- `src/formatting/event-style-timeline.lisp` (`header`): updated copyright
(`define-timeline-style`): use `:default-columns` initarg instead of `:columns`

Revision c914b347 - 07/13/2016 04:56 PM - J. Moringen

Backport: Fixed comparison of symbol values in src/formatting/protocol.lisp

refs #2601

- src/formatting/protocol.lisp (value< symbol symbol): new method;
compare symbols by name

(cherry picked from commit b92c2ce2a923e8571943290c64de8cfc48d50b9d)

Revision 408ce71c - 07/13/2016 04:56 PM - J. Moringen

Backport: Fixed :columns initarg processing in src/formatting/event-style-monitor.lisp

refs #2601

The problem was that 'monitor-style-mixin' uses a function that creates a set of columns whenever a monitor line is created. To allow supplying column specifications via the :columns initarg, such specifications have to be transformed into a suitable function.

- src/formatting/event-style-monitor.lisp (monitor-style-mixin::columns):
removed initarg; added style-%columns accessor
(monitor-style-mixin): removed :columns default initarg
(initialize-instance :before monitor-style-mixin): new method; make sure that at least one of the columns and default-columns initargs is supplied
(shared-initialize :after monitor-style-mixin t): new method; if necessary, transform list of column specification into column creation function
- src/formatting/event-style-monitor.lisp (define-monitor-style): use :default-columns initarg instead of :columns
(style-monitor/scope/tree): likewise
- src/formatting/event-style-timeline.lisp (header): updated copyright
(define-timeline-style): use :default-columns initarg instead of :columns

(cherry picked from commit 553713e8e5a59aa5f432b21b71c3f3fc52dd92b7)

Revision 75006008 - 07/13/2016 04:56 PM - J. Moringen

Backport: Fixed comparison of symbol values in src/formatting/protocol.lisp

refs #2601

- src/formatting/protocol.lisp (value< symbol symbol): new method;
compare symbols by name

(cherry picked from commit b92c2ce2a923e8571943290c64de8cfc48d50b9d)

Backport: Fixed :columns initarg processing in src/formatting/event-style-monitor.lisp

refs #2601

The problem was that `monitor-style-mixin' uses a function that creates a set of columns whenever a monitor line is created. To allow supplying column specifications via the :columns initarg, such specifications have to be transformed into a suitable function.

- src/formatting/event-style-monitor.lisp (monitor-style-mixin::columns): removed initarg; added style-%columns accessor (monitor-style-mixin): removed :columns default initarg (initialize-instance :before monitor-style-mixin): new method; make sure that at least one of the columns and default-columns initargs is supplied (shared-initialize :after monitor-style-mixin t): new method; if necessary, transform list of column specification into column creation function
- src/formatting/event-style-monitor.lisp (define-monitor-style): use :default-columns initarg instead of :columns (style-monitor/scope/tree): likewise
- src/formatting/event-style-timeline.lisp (header): updated copyright (define-timeline-style): use :default-columns initarg instead of :columns

(cherry picked from commit 553713e8e5a59aa5f432b21b71c3f3fc52dd92b7)

History

#1 - 07/13/2016 05:00 PM - J. Moringen

- *Status changed from New to Resolved*
- *% Done changed from 0 to 100*

Applied in changeset commit:rsb-tools-cl|553713e8e5a59aa5f432b21b71c3f3fc52dd92b7.