

Robotics Service Bus - Bug #399

Allow to "catch" absence of spread-daemon

06/30/2011 01:55 PM - M. Rolf

Status:	Resolved	Start date:	06/30/2011
Priority:	Normal	Due date:	
Assignee:	J. Moringen	% Done:	100%
Category:	C++	Estimated time:	0.00 hour
Target version:	0.4		
Description			
Trying to create Listeners without active spread-daemon aborts program. The attached example program fails with: 1309434238241 rsb.spread.SpreadConnection [FATAL]: spread connect error: connection to spread daemon failed due to socket errors SP_error: (-2) Could not connect. Is Spread running? terminate called after throwing an instance of 'rsc::misc::IllegalStateException' what(): Connection with id c4872aa2-500b-4e46-b0c4-e69b7c733cdd is not active. Aborted Strange things happen in memory as well (see memcheck.log and helgrind.log)			

Associated revisions

Revision 597a9de2 - 06/30/2011 03:11 PM - J. Moringen

Do not deactivate things which aren't active in Spread transport

fixes #399 (reported by Matthias Rolf)

- src/rsb/transport/spread/InConnector.cpp: when deactivating, do not try to interrupt connection in receive loop if it is not connected; do not wait for the receiver task if the connection is not connected
- src/rsb/transport/spread/SpreadConnector.cpp: when deactivating, do not deactivate the Spread connection unless it really is active

History

#1 - 06/30/2011 02:33 PM - J. Moringen

- Description updated
- Assignee set to J. Moringen
- Target version set to rsb-0.10

#2 - 06/30/2011 03:11 PM - J. Moringen

- Status changed from New to Resolved
- % Done changed from 0 to 100

Applied in changeset r1909.

#3 - 07/25/2011 06:14 PM - S. Wrede

- Target version changed from rsb-0.10 to 0.4

Files

Test.cpp	574 Bytes	06/30/2011	M. Rolf
memcheck.log	8.08 KB	06/30/2011	M. Rolf
helgrind.log	2 KB	06/30/2011	M. Rolf