

Robotics Service Bus - Tasks #565

Let RPC mechanism use cause vector

09/09/2011 12:47 PM - J. Wienke

Status:	Resolved	Start date:	09/09/2011
Priority:	Normal	Due date:	
Assignee:	J. Moringen	% Done:	100%
Category:	Protocol	Estimated time:	0.00 hour
Target version:	0.5		
Description			
<p>Now that there is a formal way to reference what caused on event, let the RPC reply event reference their request events. Has to be implemented in</p> <ul style="list-style-type: none">- C++- Java- Python- Common Lisp- Logger			
Related issues:			
Blocked by Robotics Service Bus - Enhancement # 498: Integrate causal vector ...		Closed	09/08/2011

Associated revisions

Revision 2c220b22 - 10/20/2011 09:23 PM - J. Moringen

Use cause vectors in `src/patterns/{local,remote}-server.lisp`

refs #565

- `src/patterns/local-server.lisp` (call `t local-method event`): use ``event-id/opaque'` to obtain a cause event id; add it to the reply event
- `src/patterns/remote-server.lisp`
(`self %method-listener :after t remote-method`): use ``event-id/opaque'` and cause mechanism instead of ``event-id'` and meta-data mechanism to indicate associated request
(call `t remote-method event`): extract the first cause instead of a meta-data item from the reply event; use ``%event-id->key'` to convert event id to suitable keys
(`%event-id->key`): new function; helper function for converting event ids to keys suitable for hash-table lookup

Revision 01539c5e - 10/20/2011 10:30 PM - J. Moringen

Use cause vectors in `src/rsb/patterns/{AbstractRemote,Local}Method.java`

refs #565

- `src/rsb/patterns/AbstractRemoteMethod.java`: manage in-progress call using the event ids of the request events and the causes of the reply events
- `src/rsb/patterns/LocalMethod.java`: when creating replies, use the id of the request event as cause

Revision 90998250 - 10/20/2011 10:38 PM - J. Moringen

Use cause vectors in `src/rsb/patterns/[Remote]Server.cpp`

refs #565

- src/rsb/patterns/RemoteServer.cpp: manage in-progress calls using event ids of request events and cause event ids of reply events
- src/rsb/patterns/Server.cpp: use event ids of request events as cause in reply events

Revision 5eab59af - 10/20/2011 11:47 PM - J. Moringen

Use cause vectors for RPC communication in rsb/patterns/___init__.py
refs #565

- rsb/patterns/___init__.py: in RemoteMethod, use event ids of request events and cause event ids of reply events to track in-progress method calls; in LocalMethod, add event ids of request events as causes of reply events

Revision b22adbcb - 10/21/2011 12:14 AM - J. Moringen

Adapted call-id column in formatting/columns.lisp
fixes #565

- formatting/columns.lisp (define-simple-column :call-id): print uuid derived from first cause event id

History

#1 - 09/15/2011 09:52 AM - J. Wienke

- *Subject changed from Let RPC mechanism use caus vector to Let RPC mechanism use cause vector*

#2 - 09/23/2011 02:55 PM - J. Wienke

- *Target version changed from rsb-0.10 to 0.5*

#3 - 10/20/2011 08:54 AM - J. Wienke

Jan, for this to work we should think of a CauseFilter?

#4 - 10/20/2011 03:49 PM - J. Wienke

CauseFilter is not useful here, because the filter criterion changes over time.

#5 - 10/20/2011 04:59 PM - J. Moringen

- *Category set to Protocol*
- *Status changed from New to In Progress*

#6 - 10/20/2011 05:00 PM - J. Moringen

- *Description updated*

#7 - 10/21/2011 12:19 AM - J. Moringen

- *Status changed from In Progress to Resolved*
- *% Done changed from 0 to 100*

Applied in changeset r2929.

#8 - 10/21/2011 12:20 AM - J. Moringen

- Description updated